



738259 (KCHMT29.12)

1-Door Mega Top Prep 29" Long 9-1/6, 3-1/9 Pan

Description

1-door mega top refrigerated preparation table. Exterior back panel and exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, top, sides, and interior bottom panels in 304 stainless steel, worktop in 304 stainless steel. Built-in refrigeration unit and an insulated lid to maintain food freshness. Fin & Tube Condenser improves performance in high-temperature environments. Automatic Defrost Cooling System to provide worry free performances. Full-depth cutting board of 29x9x0,5 in. Control panel, Vinyl-Coated Steel adjustable shelves, removable door gaskets and self-closing doors with 90-degree stay-open feature and on site reversible door feature, with required left side door hinges, for units with serial number 24020014 or later. Temperature range: +33/+41°F.

R290 gas in the refrigeration circuit.
ETL Safety and Sanitation certifications.
3/5 Years warranty.

Main Features

- External temperature display.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Full Depth cutting board.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Heavy duty Vinyl coated steel shelves.
- Adjustable shelves for flexible storage
- Removable rubber bumper guards for airflow spacing and shock absorption
- Back bottom mounted cooling unit guarantee an easy access and cleaning.
- Integrated polyethylene (PE) cutting board included for food-safe, durable prep surface

Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Holds (9) 1/6 & (3) 1/9 pans
- Insulated lid maintains food freshness.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic gasket removable without tools for easy cleaning.
- Self-closing door with 90-degree stay-open feature.
- Stainless steel worktop, durable functionality
- Door reversible on site

Sustainability

- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- 40 mm insulation for energy saving

Optional Accessories

PNC Code	Description
Containers, Trays and Grids	
880600	Shelf for 29" Mega Top and Salad Top Prep Table
880611	Shelf clips (4-pack)
Doors and Drawers	
880703	Door Hinge Field Reverse Kit for 27" Undercounter and Worktop & 29" Mega Top and Salad Top Prep Table
880739	Drawers Kit for 29" Mega Top and Salad Top Prep Table

Technical specifications

Electric

Supply voltage:	115 V/1 ph/60 Hz
Plug type:	USA NEMA 5-15P
Current consumption:	3 Amps
Compressor power:	1/5 hp
Power Cable Length:	2500 mm

Capacity:

Gross capacity:	7.0001 cu.feet
-----------------	----------------

Key Information:

Number and type of grids (included):	1 (636x443)
Door hinges:	Right Side
External dimensions, Width:	28 15/16" (735 mm)
External dimensions, Depth:	35 7/16" (900 mm)
External dimensions, height:	43 5/16" (1100 mm)
Number and type of doors:	1 Full
Internal Dimensions (height):	23 1/2" (597 mm)
Internal Dimensions (width):	24 1/16" (611 mm)
Net weight:	163 lbs (74 kg)
Shipping width:	30 1/2" (775 mm)
Shipping depth:	35 13/16" (910 mm)
Shipping height:	47 1/4" (1200 mm)
Shipping weight:	229 lbs (104 kg)
Type of external material:	Stainless Steel
Type of internal material:	304 AISI


Refrigeration Data

Operating temperature min.:	32 °F (0 °C)
Operating temperature max.:	41 °F (5 °C)
Defrost type:	Auto Defrost
Evaporator type	Finned
Refrigerant unit side:	Back


Sustainability

Refrigerant type:	R290
Refrigerant weight:	85 g


Front



Side



Top



EI = Electrical inlet (power)

RO = Refrigerant Outlet

RI = Refrigerant Inlet



Part of



**Electrolux
Professional
Group**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.
a. Kelvinator Commercial is a pending or registered trademark of Electrolux Consumer Products, Inc., and is used under a license from Electrolux Consumer Products, Inc.
<https://www.kelvinatorcommercial.com>

2026/08/07

3/3